



## Air Volume Instruments



Model EBT721  
(Shown with optional accessories)

### Balometer Model EBT721

The EBT721 Capture Hood is a multipurpose electronic air balancing instrument for reading air volume flow at diffusers and grilles. It is ideally suited for commissioning agents, test and balance contractors, facilities managers, health and safety specialists, and ventilation installers. This light weight, ergonomically designed kit saves time and money while helping to create a healthy and energy efficient environment.

### Features and Benefits

- Ergonomic design and ultra light weight for easy one person operation
- Detachable digital manometer for use in other applications
- Use with Pitot, air flow, temperature, velocity matrix, or relative humidity probes
- Back pressure compensation
- Bio-Safety hood kit available

### Manometer Model EBT720

The EBT720 is one of the most advanced, versatile, and easy to use manometers on the market today. Auto-zeroing allows you to make measurements throughout the day. The velocity matrix accessory is useful in measuring face velocity through filters, coils, and other specialized spaces.

### Features and Benefits

- Accurately measures pressure, velocity (Pitot), and flow
- Large, easy to read display
- Data logging and downloading software included
- Automatic density correction

*Rugged. Reliable. Professional.*



# Air Volume Instruments

Models EBT720 and EBT721



Model EBT720  
(Shown with optional accessories)

## Applications

- HVAC commissioning
- Clean room certification
- Troubleshooting HVAC systems
- Testing and balancing HVAC systems

## Optional Accessories for EBT720 AND EBT721

- Pitot tubes
- 16-point velocity matrix with telescoping handle
- Air flow probe
- Temperature probe
- Temperature/humidity probe
- Multiple hood sizes available
- Bio-safety cabinet hood kit

## Specifications

Balometer Models EBT720 and EBT721

### Velocity Range

**Pitot probes** 25 to 8,000 ft/min (0.125 to 40 m/s)  
**Air flow probe** 25 to 5,000 ft/min (0.125 to 25 m/s)  
**Velocity matrix** 25 to 2,500 ft/min (0.125 to 12.5 m/s)

### Accuracy

±3% of reading ±7 ft/min (±0.04 m/s) at velocities >50 ft/min (>0.25 m/s)

### Units

ft/min, m/s

### Resolution

1 ft/min (0.01 m/s)

### Pressure

#### Differential pressure

±15 in. H<sub>2</sub>O (±3735 Pa);  
150 in. H<sub>2</sub>O (37.5 kPa),  
maximum safe operating pressure

#### Absolute pressure

15 to 40 in. Hg (356 to 1016 mm Hg)

### Accuracy

±2% of reading ±0.001 in. H<sub>2</sub>O (±0.25 Pa) static and differential; ±2% of reading absolute

### Units

in. H<sub>2</sub>O, in. Hg, Pa, hPa, kPa, mm Hg, cm Hg, mm H<sub>2</sub>O, cm H<sub>2</sub>O,

### Resolution

0.00001 in. H<sub>2</sub>O (0.001 Pa) static and differential; 0.01 in. Hg (1 mm Hg) absolute

### Volume

#### Range

25 to 2,500 ft<sup>3</sup>/min (42 to 4250 m<sup>3</sup>/h) capture hood

### Accuracy

±3% of reading ±7 ft<sup>3</sup>/min (±12 m<sup>3</sup>/h) at flows >50 ft<sup>3</sup>/min (>85 m<sup>3</sup>/h)

### Units

ft<sup>3</sup>/min, m<sup>3</sup>/h, m<sup>3</sup>/min, l/s

### Resolution

1 ft<sup>3</sup>/min (1 m<sup>3</sup>/h)

### RH

#### Range

0 to 95% RH temperature/RH probe

### Accuracy

±3% RH

### Resolution

0.1% RH

### Temperature

#### Sensor in base

40 to 140°F (4.4 to 60°C)

#### Temperature probe

-40 to 250°F (-40 to 121°C)

#### Temperature/RH probe

14 to 140°F (-10 to 60°C)

### Accuracy

±0.5°F (±0.3°C) from 32 to 160°F (0 to 71°C)

### Units

°F, °C

### Resolution

0.1°F (0.1°C)

### Instrument Temperature Range

#### Operating

40 to 140°F (4.4 to 60°C)

#### Storage

-4 to 160°F (-20 to 71°C)

### Statistics

min, max, average up to 1000 readings

### Data Storage

1,000 readings, time and date stamped

# Air Volume Instruments

## Models EBT720 and EBT721

**Logging Interval**  
User selectable

**Response Time**  
2 to 8 seconds

**Display**  
6 digit, 0.75 in. (19 mm) character height, multi-line, sectored, multiple symbolic icons, high-contrast backlit LCD

**Dimensions (manometer only)**  
7.4 in. x 4.5 in. x 2.3 in. (18.8 cm x 11.4 cm x 5.8 cm)

**Pressure Connection**  
1/4 in. (6.35 mm) OD straight ports for use with 3/16 in. (4.76 mm) ID flexible tubing

**Weight with Batteries**  
EBT720 17 oz (0.5 kg)  
EBT721 7.4 lb (3.4 kg)

**Power Requirements**  
Four AA-size cells or AC adapter

**Hood Sizes Available (EBT721)**  
Standard 2 ft x 2 ft (610 mm x 610 mm)  
Optional 2 ft x 4 ft (610 mm x 1220 mm)  
1 ft x 4 ft (305 mm x 1220 mm)  
1 ft x 5 ft (305 mm x 1525 mm)  
3 ft x 3 ft (915 mm x 915 mm)  
**BSC Hood Kit** 8 in. x 22 in. (205 mm x 560 mm)  
10 in. x 22 in. (255 mm x 560 mm)

The BSC hood kits are used to certify Class II bio-safety cabinets by taking direct in-flow measurements for NSF compliance.



Model EBT721  
(Shown with optional BSC hood kit)

### Ordering Information

- EBT720-A1** Manometer with carrying case, 4 AA size rechargeable NiMH batteries, AC adapter, 18" Pitot probe, 2 Static Pressure probes, 16 ft. Neoprene tubing, downloading software, RS-232 interface cable, NIST-traceable calibration certificate, and manual
- EBT720-X1** -A1 plus 16-point Velocity Matrix with telescoping handle
- EBT720-01** -X1 plus Temperature Probe
- EBT720-Z1** -01 plus Relative Humidity/Temperature probe, Air Flow Probe
- EBT721-A1** 2' x 2' air capture hood/frame/base, Manometer, 4 AA size rechargeable NiMH batteries, AC Adapter, 18" Pitot probe, 2 Static Pressure probes, 16 ft Neoprene tubing, Wheeled luggage style carrying case, NIST-traceable calibration certificate, downloading software, RS-232 interface cable, and manual.
- EBT721-X1** -A1 plus 16-point Velocity Matrix with telescoping handle
- EBT721-01** -X1 plus Temperature Probe
- EBT721-Z1** -01 plus Relative Humidity/Temperature probe, Air Flow Probe

**Note:** For EBT720 or 721 with European AC adapter, change to -A2, -X2, -02, -Z2.  
For EBT720 or 721 with UK AC adapter, change to -A3, -X3, -03, -Z3  
For EBT720 or 721 with Australian AC adapter, change to -A4, -X4, -04, -Z4

	EBT720	EBT721
Air capture hood, frame and base		•
Measures air volume/flow rate	•	•
Static/Differential Pressure (air)	•	•
Air velocity, temperature, relative humidity probes (optional)	•	•
Pressure sensor	•	•
Automatic density correction	•	•
Backpressure compensation		•
Data logging (download/recall)	•	•
Field calibration	•	•
Statistics (minimum, maximum, average)	•	•
Certificate of Calibration	•	•

Specifications subject to change without notice.

**Alnor Products, TSI Incorporated** - 500 Cardigan Road Shoreview, MN 55126-3996 USA  
USA Tel: +1 800 424 7427 E-mail: customerservice@alnor.com



Contact your local Alnor Distributor or visit our website [www.alnor.com](http://www.alnor.com) for more detailed specifications.